

## Technical Data Sheet

### JAZEERA CONCRETE EFFECT PRIMER

#### JK-12006

#### Description:

A high quality developed Primer product based on a special acrylic emulsion, specially designed for application of "Jazeera Concrete Effect".

#### Recommended Use:

Recommended to be used for interior applications as a primer for "Jazeera Concrete Effect".

#### Characteristics:

- Provides high strength and durability to plaster.
- Reduces plaster cracks after drying.
- High water permeability resistance.
- High resistance to shrinkage.
- High resistance to water absorption.
- Resistance to Chemicals.
- High adhesive strength.

#### Physical Constants:

• Binder	Acrylic emulsion
• Density	1.01 kg/L.
• Solid Content	16±1% ASTM D2697
• Appearance	milky white
• D.F.T.	15 micron.
• Theoretical Spreading Rate	10 m <sup>2</sup> /L / one coat (Spreading Rate depending on the surface nature and application conditions )
• PH	7- 9

#### Surface Preparation:

- Remove any dust, dirt, grease, oil, salts, mold, loose particles or any deleterious substances which may affect adhesion.

#### Application Guide:

- "Jazeera Concrete Effect Primer" must be stirred carefully before use.
- Apply "Jazeera Concrete Effect Primer" without dilution using brush, Roller or air spray
- Apply first coat of "Jazeera Concrete Effect Primer" and leave for full dry
- Apply second coat of "Jazeera Concrete Effect Primer" then start applying "Jazeera Concrete Effect" directly in thickness of 2-3 mm Before the second layer dries .

#### Drying time:

- The drying time depends on the conditions of ventilation and the temperature.
  - Drying time: 30-60 minutes, depending on the temperature.
  - The second layer is applied after the first layer completely dry .
- Previous results according to ASTM D5895 at 25 ° C.

#### Application Tools :

- Roller.
- Brush.
- Air spray.

#### Cleaning Tools:

- Fresh water.



**Technical Data Sheet**  
**JAZEERA CONCRETE EFFECT PRIMER**  
**JK-12006**

---

**Packing:**

- Can: 3.65 Litre .

**Shelf Life & Storage:**

12 months from manufacturing date when stored in dry and shaded closed area in the original packing.

**Safety Precautions:**

- Wear protecting cloths, gloves, glasses and face protection.
- For eye contact, rinse with plenty of clean water and then seek medical advice.
- Keep away from the reach of children.
- For more details, ask for our safety data sheet for the product.

**Disclaimer:**

To the best of our knowledge the technical data listed herein is true and accurate up to publication date and is subject to change without prior notice. User must contact Jazeera Paints Company to verify of any modifications before specifying or ordering the product. Thus, information given in this sheet is not intended to be exhaustive and any person using the product other than the recommendations in this sheet or without reverting to our Jazeera TSD, he should take his accountability in this connection.

As we are not capable to control the quality and the substrate's conditions as well as the factors that affect on using, or applying the product, so we never give any written or implied guarantee in these documents, but we guarantee our products to conform to Jazeera quality while we assume no responsibility for coverage, performance or injuries resulting from application. Liability "if any" is limited to replace the products mentioned above.