

Technical Data Sheet

JAZEERA RAWA KHOTHBAN

JA-16044

Description:

A water-borne decorative topcoat paint, based on a special effect of pigment and pure acrylic emulsion to create a desert effect.

Recommended Use:

Recommended to use for interior applications on concrete, cement and gypsum surfaces of palaces, offices, showrooms, hotels, restaurants, galleries etc.

Characteristics:

- Gives impression of sand mountains in desert.
- Turns living spaces into a master showpiece.
- Very good adhesion and high durability.
- Formulated without APEOs, formaldehyde and ammonia .
- Wide range of colors.

Physical Constants:

• Finish	Metallic	
• Color	As per "Jazeera Rawa Khothban" catalog.	
• Specific Gravity	0.95	ASTM D1475.
• Viscosity	95KU	ASTM D562
• Theoretical Spreading Rate*	4-5 m ² /ltr (per coat).	

Tests:

• Heater Stability	Pass	ASTM D2243
--------------------	------	------------

*The practical spreading rate of the product depends on the surface, ambient temperature, application method, actual DFT and the wasted amount. (To avoid waste, be sure to buy the right amount of the paint for the required surface area)

Surface Preparation:

- All new concrete surfaces must be cured at least for 28 days prior to application of the primer.
- For previously painted surfaces remove old paint completely.
- The substrate should have sufficient strength and free from unsounded areas, pug holes, protrusions and pops.
- Make sure that the surface is clean , dry , free from dust, oil, grease, salt , mold and all forms release agents /curing.
- Fill the holes and cracks with suitable fillers "Jazeera Ultimate", "Jazeera Unique Filler" and "Jaz Epoxy Crack Filler ESP" prior to application of the primer (Refer to TSD)

Application Guide:

1. The required temperature during application, must not be less than 5°C; the surface moisture should not exceed 8% and the relative humidity at work place should not exceed 70%.
2. pH of surface should not exceed 9.
3. Paint should be stirred carefully before use.
4. Do not apply on wet and moistened surfaces until completely dry.
5. Do not apply the next coat unless the previous one is fully dry. Minimum recoating interval time should be followed.
6. Adequate ventilation should be provided during application.

Application Tools:

Brush: Special type

Thinner:

Not recommended.

Thinning Ratio:

Ready to use.

Technical Data Sheet

JAZEERA RAWA KHOTHBAN

JA-16044

Painting System:

- Apply one coat of "Jazeera Green Prime".
- Apply two coats of "Jazeera Green Putty".
- Apply two coats of "Jazeera Semi Gloss Deco Primer", of the same color as that of "Jazeera Rawa Khotbhan" (topcoat), by using a fine roller or spray gun and make sure that surface is uniform and there are no roller marks.
- The color of "Jazeera Semi Gloss Deco Primer" must always be the same as "Jazeera Rawa Khotbhan" (topcoat).
- Apply one coat of product obliquely or horizontally in zigzag movement with the help of special recommended brush.

Drying Time:

- Surface dry (15 - 20) minutes.
- Hard dry 5 hours.
- Full cure 7 days.

All above test results according to ASTM D5895@25OC.

Cleaning Tools:

Tap Water.

Packing:

Plastic container : 3 liters.

Storage and Shelf Life:

Shelf life: 24 months @ 25 °C.

Storage: The container should be kept in sealed, dry, cool, well-ventilated place and stored in accordance with national regulations.

Safety Precaution:

Please read and follow the precautionary notices displayed on the container, and all caution statements on the MSDS of this product.

- Handle with care before and during use.
- During application of paint, contact of liquid paint with eyes, skin, inhalation of paint mist and paint vapour, should be strongly avoided.
- Recommended to use the product in well-ventilated area when applying the paint in insufficient ventilated areas, forced ventilation should be provided.
- Keep away from the reach of children.

For environmental safety: please donate the leftover paint and packaging to your local authorized institution for usage or recycling purpose.

Disclaimer:

To the best of our knowledge the technical data listed herein is true and accurate up to publication date and is subject to change without prior notice. User must contact Jazeera Paints Company to verify of any modifications before specifying or ordering the product. Thus, information given in this sheet is not intended to be exhaustive and any person using the product other than the recommendations in this sheet or without reverting to our Jazeera TSD, he should take his accountability in this connection.

As we are not capable to control the quality and the substrate's conditions as well as the factors that affect on using, or applying the product, so we never give any written or implied guarantee in these documents, but we guarantee our products to conform to Jazeera quality while we assume no responsibility for coverage, performance or injuries resulting from application. Liability "if any" is limited to replace the products mentioned above.