

Technical Data Sheet
JAZEERA MINI PAINT
JF- 11446

Description:

A high-quality water-based topcoat paint with a comfortable visual of gloss level, filled in a special pack that allows application in a practical and easy way with a smooth touch, it can be used by the customer without need for qualified technicians, facilitates the process of choosing and matching color before tinting the products in large quantities for the entire area and purchase without hesitation.

Recommended Use :

Recommended to use for interior applications on concrete, cement and applied surfaces by putties, where required to try the color in place for ensuring color choice prior to purchase for whole area.

Characteristics :

- Quick, easy and professional way to choose a color before painting the entire area.
- Determining the final color with complete conviction by applying in place.
- Easy to apply, no need for painting skill or any application tool.
- Suitable for choosing and matching colors in projects.
- Saves time and cost in choosing the desired color for the final product.
- Comfortable visual of gloss level.
- Gives a smooth finish without roller marks.
- Free from VOC, formaldehyde, ammonia and APEOs.
- Environmentally responsible.

Physical Constants:

• Finish:	Sheen, ideal gloss level.	
• Color:	Selected colors	
• Volume Solid:	42 %	ASTM D2697
• DFT.:	30-40 μ	
• Theoretical Spreading Rate:	0.32-0.42 m ² per can 30ml.	
• Freeze-Thaw Stability:	Pass, 3 cycles	ASTM D2243

Surface Preparation :

- Make sure that the surface is clean, dry, free from dust, oil, grease, salt and mold.
- The substrate should have sufficient strength and free from unsounded areas, pug holes, protrusions and pops.
- All new surfaces shall be cured at least 28 days prior to application of the primer.

Application Conditions:

- The required temperature during application, must not be less than 5°C; the surface moisture should not exceed 8% and the relative humidity at work place should not exceed 70%.
- pH of surface should not exceed 9.
- Do not apply on wet and moistened surfaces until completely dry.

Instructions:

- Shake the can well before opening the cover.
- Remove the foil under roller.
- Start application on the desired surface by pressing gently at an angle of 45°C.
- For best results, apply 2 coats of the product, 30minutes of recoating interval should be followed.
- To avoid dryness, use the product after opening.
- The degree of gloss may cause a slight change in the color shade.
- For color matching, allow the product to dry.

Thinner :

Not recommended.

Application Tools :

- The product can is convenient for direct application.



Technical Data Sheet
JAZEERA MINI PAINT
JF- 11446

Drying Time:

- Surface dry : 20 min.
- Recoating interval : 30 min.
- Hard dry : 4 hours.
- Full cure : 7 days.

All above results according to ASTM D5895 @ 25°C.

Cleaning Tools:

The roller of can may be cleaned after use with fresh water.

Packing:

Can 30 ml.

Shelf Life and Storage:

Shelf life: 24 months @ 25 °C.

Storage: The container should be sealed and kept in dry, cool & well-ventilated place and stored in accordance with national regulations.

Safety Precautions:

- Please read and follow the precautionary notices displayed on the container, and all caution statements on the MSDS of this product.
- Handle with care before and during use.
- During application of paint, contact of liquid paint with eyes, skin, inhalation of paint mist and paint vapour, should be strongly avoided.
- Recommended to use the product in well-ventilated area when applying the paint in insufficient ventilated areas, forced ventilation should be provided.
- Keep away from the reach of children.

For environmental safety: please donate the leftover paint and packaging to your local authorized institution for usage or recycling purpose.

Note: Wastes and empty containers should be disposed of in accordance with local regulations made under the Control of Pollution Act and the Environmental Protection Act.

Disclaimer:

To the best of our knowledge the technical data listed herein is true and accurate up to publication date and is subject to change without prior notice. User must contact Jazeera Paints Company to verify of any modifications before specifying or ordering the product. Thus, information given in this sheet is not intended to be exhaustive and any person using the product other than the recommendations in this sheet or without reverting to our Jazeera TSD, he should take his accountability in this connection.

As we are not capable to control the quality and the substrate's conditions as well as the factors that affect on using, or applying the product, so we never give any written or implied guarantee in these documents, but we guarantee our products to conform to Jazeera quality while we assume no responsibility for coverage, performance or injuries resulting from application. Liability "if any" is limited to replace the products mentioned above.