



MATERIAL SAFETY DATA SHEET

JA-37001

JAZETAL SEMI GLOSS

Version No:4 Revision Date: 26/4/2021

1. PRODUCT & COMPANY IDENTIFICATION

PRODUCT NAME	JAZETAL SEMI GLOSS
PRODUCT CODE	JA-37001
PRODUCT DESCRIPTION	See Technical Data Sheet
RECOMMENDED USE	See Technical Data Sheet

COMPANY IDENTIFICATION

COMPANY NAME:	JAZEERA FACTORY FOR PAINTS CO.
COUNTRY:	SAUDI ARABIA
CITY:	KHAMIS MUSHAYT.61961
P.O. BOX:	1900
TEL:	+ 966 17 221 1111
FAX:	+ 966 17 238 2728

2. COMPOSITION / INFORMATION ON INGREDIENTS

MATERIAL OR COMPONENT	CAS NO	R PHRASES	WEIGHT%
Titanium dioxide	13463-67-7	-	15-22 %
Alkyd Resin	Not hazardous	-	20-30 %
White Spirit	64742-48-9	-	25-35 %
Calcium Carbonate	Not hazardous	36,37,38	25-35 %

3. HAZARD IDENTIFICATION

Primary routes of exposure

- Inhalation
- Eye Contact
- Skin Contact

Effects of Exposure: Vapor , mist , dust is harmful to skin , mucous membrane , eyes & respiratory system irritation.

HEALTH HAZARDS:

Primary Routes of Exposure

Skin Absorption None currently know.

Inhalation In high concentration may cause drowsiness.

Eye Contact Excess redness and swelling of the conjunctiva may occur. Does not injure eye tissues. Cause irritation, experienced as stinging and discomfort or pain.

Skin Contact Contact may irritate or burn the skin. Prolonged contact causes mild to moderate local redness and swelling.

Effect of repeated over exposure Non-evidence of adverse effect from available information



MATERIAL SAFETY DATA SHEET

JA-37001

JAZETAL SEMI GLOSS

Version No:4 Revision Date: 26/4/2021

4. FIRST AID MEASURES

Swallowing

Do not induce vomiting. Keep patient at rest. Seeking immediate medical attention.

Inhalation

Move victim to fresh air, call emergency medical care. If not breathing give artificial respiration. If breathing is difficult give oxygen. Get prompt medical attention.

Eye Contact

Immediately flush eyes with a large amount of water for at least 15 minutes. Get prompt medical attention.

Skin Contact

Remove contaminated clothing. Wash affected skin areas thoroughly with soap and water. See a physician.

5. FIRE FIGHTING MEASURES

Flash Point: = 38 °C ASTM D-56

Unusual Hazard

Vapors can travel to a source of ignition and flash back.

Heated material can form flammable or explosive vapors with air. Toxic fumes are generated when material is exposed to fire or fire condition.

Extinguishing Agents

Use the following extinguishing media when fighting fires involving this material:

Polar solvent (alcohols) foam – carbon dioxide – water spray – dry chemical

Small fire

Use dry chemical powder, CO2 foam and water supply.

Large Fire

Use water spray, fog or foam, Move containers or drums from fire areas, if you can do it without risk.

Cool containers that are exposed to flames with water from the sides until and after fire is out.

Personal Protective Equipment

Wear self – contained breathing apparatus and full protective clothing.

Special Procedures

Use water spray to cool containers exposed to fire.

6. ACCIDENT RELEASE MEASURES

SAFETY PRECAUTIONS

- Open enclosed spaces to outside atmosphere.



MATERIAL SAFETY DATA SHEET

JA-37001

JAZETAL SEMI GLOSS

Version No:4 Revision Date: 26/4/2021

- Wear protective clothing, boots, gloves & eye protection.
- Consult the safety measures listed under headings 7 and 8.

ENVIRONMENTAL PRECAUTIONS

Control the leaks & spills with non-combustible absorbent material such as

- Sand
- Earth
- Vermiculite.
- Diatom earth in drums for waste disposal.

CLEANING METHODS

If recovery is not visible :

- Admix with dry soil, sand or non-reactive absorbent & place in an appropriate chemical waste container.
- Transfer to containers by suction, preparatory for later disposal.
- Flush area with water spray.
- Clean – up personnel must be equipped with self-contained breathing apparatus & butyl rubber protective clothing.
- For large spills, recover spill material with a vacuum truck.

7. HANDLING & STORAGE

Handling & Storage Precautions

Keep container closed upright when not in use. Store in cool, dry, well ventilated area.
Avoid storage temperature above 100 Degrees Fahrenheit.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

TECHNICAL MEASURES

Ensure adequate ventilation, if possible with extractor fans at workplace & appropriate

general extraction. Personnel should wear regularly laundered overalls.

If this ventilation is insufficient to maintain concentration of fumes below the exposure limits, wear breathing apparatus.

SAFETY BREATHING APPARATUS

Where workers encounter concentrations higher than the exposure limits, they must wear suitable, approved masks.

HAND PROTECTION

Protective creams may be used for exposed skin, but they should not be applied after contact with the product. In the event of the prolonged or repeated contact with the hands, use appropriate gloves.

EYE AND FACE PROTECTION

Use eye protectors designed to protect against liquid splashes.



MATERIAL SAFETY DATA SHEET

JA-37001

JAZETAL SEMI GLOSS

Version No:4 Revision Date: 26/4/2021

9. PHYSICAL AND CHEMICAL PROPERTIES

Color	Colors
State	Liquid
Odor	Usual to solvent
pH	Not Applicable
Flash Point	38 °C
Specific Gravity (Water = 1)	1.3-1.4
Vapor Pressure	Not defined
Vapor Density (Air = 1)	-
Melting Point	-
Boiling Point	150-205 °C (/60mmHg)
Solubility in water	Immiscible
Evaporation Rate (Butyl Acetate = 1)	550
Lead content (%)	Nil

10. STABILITY AND REACTIVITY

Instability This material is considered stable. However, avoid contact with ignition sources (e.g. sparks, flame, heated surfaces).

Hazardous Combustion or Decomposition Product

Burning may produce carbon monoxide, carbon dioxide. When heated it emits irritating fumes, can react vigorously with oxidizing materials.

Hazardous Polymerization Product will not undergo polymerization.

Incompatibility Avoid contact with strong oxidizing agent.

11. TOXICOLOGICAL INFORMATION

Acute Date

The following information is based on toxicity profiles of the most potentially hazardous component of this material.

LD50 Oral : >5.0 g/Kg rats

LD50 Skin Contact : >3.0 g/Kg rabbits

LD50 inhalation : > Not estimated.

Longer inhalation of concentrated solvent in the product which exceed the threshold limit value (150) could cause irritation of mucous tissues of respiratory system or even affect normal functioning of kidney, liver and central nervous system. Ingestion can damage the tissue of the digestive system. Longer and intensive contact with skin can cause the loss of subcutaneous skin fat and dermatitis.

12. ECOLOGICAL INFORMATION

- The product contains 100% of volatile organic components in total of the regulation



MATERIAL SAFETY DATA SHEET

JA-37001

JAZETAL SEMI GLOSS

Version No:4 Revision Date: 26/4/2021

relating to the emission of substances in air.

- Biodegradability of the product in the natural in the natural environment is relatively long.
- Prevent spillage on soil, in water streams, water reserves, sewage systems and biological water treatment facilities.

13. DISPOSAL CONSIDERATION

Spill Release Procedure

Avoid breathing of vapors or dust. Use absorbent clean-up materials or sweep up. Place in separate container. Keep out of public sewers & waterways. If entry is threatened or occurs, notify local authorities. Eliminate all sources of ignition.

Waste Disposal Methods

In separate closed metal container in accordance with all applicable regulations.

Other Precautions

Do not take internally, avoid prolonged breathing of vapors or dust or spray mist or contact with skin & eyes. Do not welds or flame cut an empty container, Ground containers when pouring? Destroy contaminated leather & absorbent shoes.

14. TRASPORT INFORMATION

Land Transport (ADG)

Class : 3

Labeling of vehicles – hazard code: 90 UN No. :1263

Symbol of hazard : 3

Sea Transport (IMDG)

IMO PSN Code : LCT

IMO Proper Shipping name : Paint or Paint related material.

UN Hazard Class : 3 UN Number1263

Air Transport (IATA)

IATA Label : Flammable liquid.

Symbol of Hazard : 3

UN Hazard Class : 3 UN Number1263

15. STATUTORY / REGULATORY INFORMATION

- This preparation is classified in compliance with the directive known as " All preparations " 1999 / 45 / EC.
- In addition directive 2001 59 / EC with the 28 adoption of directive 67 / 548 / EC (Hazardous substances) have been taken into account.
- PARTICULAR HAZARDS ASSOCIATED WITH THE PRODUCT AND SAFETY RECOMMENDATIONS:
 - R 22 Harmful if swallowed
 - R 36 / 38 Irritating to eyes and skin.



MATERIAL SAFETY DATA SHEET

JA-37001

JAZETAL SEMI GLOSS

Version No:4 Revision Date: 26/4/2021

- R 51 / 53 Toxic to aquatic organisms, may cause long-term adverse effect in the aquatic environment.
- S 23 Do not breathe vapor or spray.
- S 24 Avoid contact with skin.
- S 62 If swallowed do not induce vomiting, seek medical advice.fy

16. OTHER INFORMATION

- Since the end users working conditions are not known by us the information provided in this safety data sheet is based on our current level of knowledge.
- The information provided in this safety data sheet relates to the product in the state in which it is delivered.
- It is intended to describe our products from the point of view of safety requirements & is not intended to guarantee any particular properties.
- The product must not be used for any purpose other than those specified under heading without first obtaining written handling instructions.
- It is all times the responsibility of the users to take all necessary measures to comply with legal requirements & local regulations.
- The information given in this safety data sheet must be regarded as a description of the safety requirements relating to our product and not guarantee of its properties.