

MATERIAL SAFETY DATA SHEET **JA-16053** JAZEERA MAXIM SILK Version No: 4 Revision Date: 19/4/2021 **PRODUCT & COMPANY IDENTIFICATION PRODUCT NAME** JAZEERA MAXIM SILK **PRODUCT CODE** JA-16053 **PRODUCT DESCRIPTION** See Technical Support Department See Technical Support Department **RECOMMENDED USE COMPANY IDENTIFICATION COMPANY NAME:** JAZEERA FACTORY FOR PAINTS CO. **COUNTRY:** SAUDI ARABIA **CITY: KHAMIS MUSHAYT.61961** P.O. BOX: 1900 + 966 17 221 1111 + 966 17 238 2728 2. COMPOSITION / INFORMATION ON INGREDIENTS MATERIAL OR COMPON

MATERIAL OR COMPONENT	CAS NO	R PHRASES	WEIGHT%	
Titanium dioxide	13463-67-7		15%-20 %	
Precipitated Barium Sulphate	Not hazardous		2-4 %	
Aqua Ammonia	1336-21-6	34,50	<0.2 %	
Pure Acrylic 100%	Not hazardous		55%-65 %	
5-chloro-2-methyl-4-isothiazolin-3-o	ne			
and 2-methyl-2H-isothiazol-3-one	55965-84-9	23/24/25	0.1%-0.25 %	
				_

3. HAZARD IDENTIFICATION

This preparation is not classed as flammable, hazardous to health by directive 1999/45/EC. Primary routes of exposure

- Inhalation
- Eye Contact _
- Skin Contact

Inhalation

1.

TEL: FAX:

Inhalation of vapor or mist may cause headache, nausea, and irritation of nose, throat & lungs **Eye Contact**

Direct contact with eye may cause slight irritation.

Skin Contact

Prolonged or repeated skin contact can cause slight skin irritation.



MATERIAL SAFETY DATA SHEET JA-16053 JAZEERA MAXIM SILK Version No: 4 Revision Date: 19/4/2021

4. FIRST AID MEASURES

Inhalation

Move the patient to the fresh air.

Eye Contact

Flush eyes with fresh water for at least 15 minutes. Consult a physician if irritation persists.

Skin Contact

Wash skin with soap & fresh water. Consult a physician if irritation persists.

Ingestion

If swallowed rinse the mouth with water & give 2 glasses of water to drink. Consult to physician. Never give anything by mouth to an unconscious person.

5. FIRE FIGHTING MEASURES

Flash Point : Auto ignition Temp. : Upper explosive limit : Lower explosive limit : Non-Combustible Not Applicable Not Applicable Not Applicable

Unusual Hazard

Dried film can burn & may generate toxic, irritating & combustion products.

Extinguishing Agent

Use extinguishing media appropriate to surrounding fire.

Personal Protective Equipment

Wear self-contained breathing apparatus (autonomous insulating breathing apparatus) & full protective body suit.

6. ACCIDENT RELEASE MEASURES

SAFETY PRECAUTIONS

- Open enclosed spaces to outside atmosphere.
- Wear protective clothing, boots, gloves & eye protection.
- Consult the safety measures listed under headings 7 and 8.

ENVIRONMENTAL PRECAUTIONS

Control the leaks & spills with non-combustible absorbent material such as

- Sand
- Earth
- Vermiculite.
- Diatom earth in drums for waste disposal.



MATERIAL SAFETY DATA SHEET JA-16053

JAZEERA MAXIM SILK

Version No: 4 Revision Date: 19/4/2021

CLEANING METHODS

If recovery is not visible :

- Admix with dry soil, sand or non-reactive absorbent & place in an appropriate chemical waste container.
- Transfer to containers by suction, preparatory for later disposal.
- Flush area with water spray.
- Clean up personnel must be equipped with self-contained breathing apparatus & butyl rubber protective clothing.
- For large spills, recover spill material with a vacuum truck.

7. HANDLING & STORAGE

Handling & Storage Precautions

Keep container closed upright when not in use. Store in cool, dry, well ventilated area. Avoid storage temperature above 100 Degrees Fahrenheit.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

TECHNICAL MEASURES

Ensure adequate ventilation, if possible with extractor fans at workplace & appropriate general extraction.

Personnel should wear regularly laundered overalls.

If this ventilation is insufficient to maintain concentration of fumes below the exposure limits, wear breathing apparatus.

SAFETY BREATHING APPARATUS

Where workers encounter concentrations higher than the exposure limits, they must wear suitable, approved masks.

HAND PROTECTION

Protective creams may be used for exposed skin, but they should not be applied after contact with the product. In the event of the prolonged or repeated contact with the hands, use appropriate gloves.

EYE AND FACE PROTECTION

Use eye protectors designed to protect against liquid splashes.

9. PHYSICAL AND CHEMICAL PROPERTIES

Viscosity Specific Gravity		90 KU @ 25°C ASTM D-562 1.26 @ 25°C ASTM D-1475
pH	:	9±0.5
Solubility	:	Water
Color	:	White & other colors as per shade card.
Flash point	:	Not applicable.



MATERIAL SAFETY DATA SHEET JA-16053 JAZEERA MAXIM SILK

Version No: 4 Revision Date: 19/4/2021

10. STABILITY AND REACTIVITY

STABILITY	
INCOMPATIBILITY	
POLYMERIZATION	
REACTIVITY	

12 Months in dry, cool & well ventilated place. Any other solvent except water. Polymerization will not occur. Not applicable.

11. TOXICOLOGICAL INFORMATION

:

:

:

There is no data available on this product.

12. ECOLOGICAL INFORMATION

There is no data available on this product.

13. DISPOSAL CONSIDERATION

Spill Release Procedure

Avoid breathing of vapors or dust. Use absorbent clean-up materials or sweep up. Place in separate container. Keep out of public sewers & waterways. If entry is threatened or occurs, notify local authorities. Eliminate all sources of ignition.

Waste Disposal Methods

In separate closed metal container in accordance with all applicable regulations.

Other Precautions

Do not take internally, avoid prolonged breathing of vapors or dust or spray mist or contact with skin & eyes. Do not welds or flame cut an empty container, Ground containers when pouring? Destroy contaminated leather & absorbent shoes.

14. TRASPORT INFORMATION

Not classified as " Hazardous for Transport. "

15. STATUTORY / REGULATORY INFORMATION

- This preparation is classified in compliance with the directive known as " All preparations " 1999 / 45 / EC.
- In addition directive 2001 59 / EC with the 28 adoption of directive 67 / 548 / EC (Hazardous substances) have been taken into account.
- PERTICULAR HAZARDS ASSOCIATED WITH THE PRODUCT AND SAFETY RECOMMENDATIONS:



MATERIAL SAFETY DATA SHEET JA-16053 JAZEERA MAXIM SILK Version No: 4 Revision Date: 19/4/2021

- R 22 Harmful if swallowed
- R 36 / 38 Irritating to eyes and skin.
- R 51 / 53 Toxic to aquatic organisms, may cause long-term adverse effect in the aquatic environment.
- S 23 Do not breathe vapor or spray.
- S 24 Avoid contact with skin.
- S 62 If swallowed do not induce vomiting, seek medical advice.

16.OTHER INFORMATION

- Since the end users working conditions are not known by us the information provided in this safety data sheet is based on our current level of knowledge.
- The information provided in this safety data sheet relates to the product in the state in which it is delivered.
- It is intended to describe our products from the point of view of safety requirements & is not intended to guarantee any particular properties.
- The product must not be used for any purpose other than those specified under heading without first obtaining written handling instructions.
- It is all times the responsibility of the users to take all necessary measures to comply with legal requirements & local regulations.
- The information given in this safety data sheet must be regarded as a description of the safety requirements relating to our product and not guarantee of its properties.

