



**MATERIAL SAFETY DATA SHEET**  
**JT-22002**  
**JAZEERA PAINT REMOVER**  
**Version No: 4 Revision Date 20/4/2021**

**1. PRODUCT & COMPANY IDENTIFICATION**

<b>PRODUCT NAME</b>	JAZEERA PAINT REMOVER
<b>PRODUCT CODE</b>	JT-22002
<b>PRODUCT DESCRIPTION</b>	See Technical Data Sheet
<b>RECOMMENDED USE</b>	See Technical Data Sheet

**COMPANY IDENTIFICATION**

<b>COMPANY NAME:</b>	JAZEERA FACTORY FOR PAINTS CO.
<b>COUNTRY:</b>	SAUDI ARABIA
<b>CITY:</b>	KHAMIS MUSHAYT.61961
<b>P. O. BOX:</b>	1900
<b>TEL:</b>	+ 966 17 221 1111
<b>FAX:</b>	+ 966 17 238 2728

**2. COMPOSITION / INFORMATION ON INGREDIENTS**

MATERIAL OR COMPONENT	CAS NO	OSHA PEL	AGGIH TLV	WT%
Dichloro Methane	75-09-2	25 PPM	50 PPM	80-85
Toluene	108-88-3	200PPM	-	~5

**3. HAZARD IDENTIFICATION**

Primary routes of exposure

- Inhalation
- Eye Contact
- Skin Contact

Effects of Exposure: Heated product may produce inhalable vapors.

**HEALTH HAZARDS:**

**SKIN IRRITATION:** Irritant.

**EYE IRRITATION:** Irritant.

**SENSITIZATION:** Possible in susceptible individuals.



## MATERIAL SAFETY DATA SHEET

JT-22002

### JAZEERA PAINT REMOVER

Version No: 4 Revision Date 20/4/2021

**SIGNS AND SYMPTIONS OF OVEREXPOSURE:** Skin and eye irritation and allergic skin and respiratory reactions.

**MEDICAL COND AGGRAVATED BY EXPOSURE:** Skin and eye conditions.

#### 4. FIRST AID MEASURES

##### Eyes Contact

Immediately flush eyes with water for at least 15 minutes. Call a physician.

##### Skin Contact

Wash with soap and water. Remove contaminated clothing and launder before re- use.

##### Ingestion

If conscious, give plenty of water to drink. do not induce vomiting. Call a physician.

##### Inhalation

Remove to fresh air. Give oxygen and/or artificial respiration, if needed. Call a Physician

##### Other

Referral to a physician is recommended if there is any question about the seriousness or any injury.

#### 5. FIRE FIGHTING MEASURES

**FLASH POINT:** = 7 °C ASTM D-56

**EXTINGUISHING MEDIA:** CO<sub>2</sub>, DRY CHEMICAL, FOAM.

**FIRE FIGHTING PROCEDURES:** USE SELF-CONTAINED BREATHING APPARATUS.

**UNUSUAL FIRE/EXPLOSION HAZARD:** DECOMPOSITION & COMBUSTION PRODUCTS MAY BE TOXIC.

#### 6. ACCIDENT RELEASE MEASURES

##### SAFETY PRECAUTION

- Open enclosed spaces to outside atmosphere.
- Wear protective clothing, boots, gloves & eye protection.
- Consult the safety measures listed under headings 7 & 8.

##### SPILL RELEASE PROCEDURES:

Remove spillage by absorbing in nonreactive absorbent material.

##### WASTE DISPOSAL METHODS:

Consult qualified local or corporate personnel for method that will comply with local, state and federal health and environmental regulations.



## MATERIAL SAFETY DATA SHEET

JT-22002

### JAZEERA PAINT REMOVER

Version No: 4 Revision Date 20/4/2021

#### 7. HANDLING & STORAGE

##### Spill Release Procedure

Avoid breathing of vapors or dust. Use absorbent clean-up materials or sweep up. Place in separate container. Keep out of public sewers & waterways. If entry is threatened or occurs, notify local authorities. Eliminate all sources of ignition.

##### Waste Disposal Methods

In separate closed metal container in accordance with all applicable regulations.

##### Handling & Storage Precautions

Keep container closed upright when not in use. Store in cool, dry, well-ventilated area. Avoid storage temperature above 100 Degrees Fahrenheit.

##### Other Precautions

Do not take internally. Avoid prolonged breathing of vapors or dust or spray mist or contact with skin & eyes. Do not weld or flame cut an empty container. Ground containers when pouring. Destroy contaminated leather & absorbent shoes.

#### 8. EXPOSURE CONTROL / PERSONAL PROTECTION

##### Respiratory Protection

Use NIOSH approved organic vapor cartridge respirator when vapor/mist exposure is likely. Use air-line respirators in confined or restricted ventilation areas. Refer to 29 CFR, OSHA parts 1910, 1915, and 1916 for coating operations.

##### Ventilation

General mechanical and local exhaust in accordance with ACGIH recommendations.

##### Protective Gloves

Wear impermeable gloves.

##### Eye Protection

Wear splash-proof chemical goggles

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

**Spec Gravity:** 1.20 (WATER = 1)

**Solubility :** aromatic hydrocarbon, ester, ketones.

**Insolubility:** water, aliphatic hydrocarbon.

**Appearance and Odor :** clear

**Percent Volatiles by Volume :**  $52 \pm 2$  %

#### 10. STABILITY AND REACTIVITY

**Stability Indicator:** Yes



## MATERIAL SAFETY DATA SHEET

JT-22002

### JAZEERA PAINT REMOVER

Version No: 4 Revision Date 20/4/2021

**Stability Condition To Avoid:** Elevated Temperatures.

**Materials To Avoid :** Strong oxidizing agents, mineral acids, and bases.

**Hazardous Decomposition Products:** Carbon monoxide, carbon dioxide and oxides of nitrogen.

**Hazardous Polymerization Indicator:** No

#### 11. TOXICOLOGICAL INFORMATION

No toxicological information is available for this product.

#### 12. ECOLOGICAL INFORMATION

Nuisance dust may be generated when sanding or sawing cured material.

#### 13. DISPOSAL CONSIDERATION

##### Spill Release Procedure

Avoid breathing of vapours or dust. Use absorbent clean-up materials or sweep up. Place in separate container. Keep out of public sewers & waterways. If entry is threatened or occurs , notify local authorities. Eliminate all sources of ignition.

##### Waste Disposal Methods

In separate closed metal container in accordance with all applicable regulations.

##### Handling & Storage Precautions

Keep container closed upright when not in use. Store in cool , dry , well ventilated area. Avoid storage temperature above 100 Degrees Fahrenheit.

##### Other Precautions

Do not take internally. Avoid prolonged breathing of vapors or dust or spray mist or contact with skin & eyes. Do not weld or flame cut an empty container. Ground containers when pouring. Destroy contaminated leather & absorbent shoes.

#### 14. TRASPOT INFORMATION

##### Land Transport (ADG)

Class : 3

Labeling of vehicles – hazard code : 90 UN No. :1263

Symbol of hazard : 3

##### Sea Transport ( IMDG )

IMO PSN Code : LCT



## MATERIAL SAFETY DATA SHEET

JT-22002

### JAZEERA PAINT REMOVER

Version No: 4 Revision Date 20/4/2021

IMO Proper Shipping name : Paint or Paint related material.

UN Hazard Class : 3 UN Number1263

**Air Transport ( IATA )**

IATA Label : Flammable liquid.

Symbol of Hazard : 3

UN Hazard Class : 3 UN Number1263

Product name : Al-Jazeera Tetra Zinc L1

#### 15. STATUTORY / REGULATORY INFORMATION

According to the regulations, the following danger labeling of the product is required.

- The Text **Flammable**
- Danger labeling **Xn** and text Harmful, contains Xylene

**R Phrases**

- R 10 Flammable
- R 20/21 Harmful by inhalation and in contact with skin
- R 51 Irritating to skin

**S Phrases**

- S 7/9 Keep container tightly closed in well-ventilated place.
- S 36/37/39 Wear suitable clothing's, gloves and eye/face protection.
- S 51 Use only in ventilated areas.

#### 16. OTHER INFORMATION

- Since the end users working conditions are not known by us the information provided in this safety data sheet is based on our current level of knowledge.
- The information provided in this safety data sheet relates to the product in the state in which it is delivered.
- It is intended to describe our products from the point of view of safety requirements & is not intended to guarantee any particular properties.
- The product must not be used for any purpose other than those specified under heading without first obtaining written handling instructions.
- It is all times the responsibility of the users to take all necessary measures to comply with legal requirements & local regulations.
- The information given in this safety data sheet must be regarded as a description of the safety requirements relating to our product and not guarantee of its properties.