

Technical Data Sheet

JAZEERA SALD

JA-25043

Description:

A high quality water borne texture topcoat paint, based on pure acrylic emulsion and natural aggregates to withstand harsh Middle East climate.

Recommended Use:

Recommended to use for exterior and interior applications on concrete, cement and brick surfaces of educational institutions, residential, commercial and industrial buildings.

Characteristics:

- Imparts elegance and beautiful appearance to buildings.
- High resistance to UV.
- Excellent resistance to alkali and water.
- Good spreading rate.
- High resistance to harsh Middle East weather conditions.
- Free from formaldehyde, ammonia and APEOs.

Physical Constants:

• Finish	Multi-color texture	
• Color	As per "Jazeera Sald" catalog.	
• Specific Gravity	1.7	ASTM D1475.
• Volume Solid	52 +/-0.5 %	ASTM D2697
• Freeze-thaw stability	Pass	ASTM D2243.
• Heater stability	Pass 30 days @ 50°C	
• Theoretical SpreadingRate*	(0.3-0.43) m ² / Kg @ DFT 700-1000 micron	
• VOC	32.96 g/L	

*The practical spreading rate of the product depends on the surface, ambient temperature, application method, actual DFT and the wasted amount. (To avoid waste, be sure to buy the right amount of the paint for the required surface area).

Surface Preparation:

- All new surfaces shall be cured at least 28 days prior to application of the primer.
- Remove old paints completely from previously painted surfaces.
- The substrate should have sufficient strength and free from unsounded areas, pug holes, protrusions and pops.
- Make sure that the surface is clean, dry, free from dust, oil, grease, salt and mold.
- Fill the holes and cracks with suitable fillers such as "Jazeera Ultimate", "Jazeera Unique Filler" or "Jazeera Epoxy Crack Filler 400" prior to application of the primer (Refer to TSD).

Application Guide:

- The required temperature during application, must not be less than 5°C; the surface moisture should not exceed 8% and the relative humidity at work place should not exceed 70%.
- pH of surface should not exceed 9.
- Paint should be stirred carefully before use.
- A suitable quantity of "Tap water" can be added to get reasonable viscosity for application.
- Do not apply on wet and moistened surfaces until completely dry.
- Do not apply the next coat unless the previous one is fully dry. Minimum recoating interval time should be followed.

Technical Data Sheet

JAZEERA SALD

JA-25043

Application Tools:

- Air spray Gun: Texture spray gun
Nozzle size medium : 4.5 mm
Air pressure : 80-100 psi
- Plastic roller smooth
- Stainless steel / plastic trowel

Thinner:

“Tap Water”.

Thinning Ratio:

(0-3)%.

Depending on the weather and application conditions.

Painting System:

- Apply one coat of "Jazeera C Primer" if required.
- Apply two coats of "Jazeera Royal Prime" according to "Jazeera Sald" color and leave it for drying.
- Apply "Jazeera Sald" with special texture gun to achieve uniform spreading and evenly thickness.
- Press with smooth stainless steel or plastic trowel or plastic roller after touch dry then let it for drying.
- Apply 2-3 coats of "Jazeera Sald Clear" after hard dry (72 hours).
- For aesthetic appearance, the facades should be cut and the frames fixed before applying the product.

Drying Time:

- Surface dry 2 hours.
- Hard dry 72 hours.
- Full cure 7 days.

All above test results according to ASTM D5895.@25°C

Cleaning Tools:

Sponge saturated with tap water.

Packing:

Drum 25 Kg.

Shelf Life & Storage:

Shelf life : 12 months @ 25 °C.

Storage: The container should be kept in sealed, dry, cool, well -ventilated place and stored in accordance with national regulations.

Technical Data Sheet

JAZEERA SALD

JA-25043

Safety Precautions:

Please read and follow the precautionary notices displayed on the container, and all caution statements on the MSDS of this product.

- Handle with care before and during use.
- During application of paint, contact of liquid paint with eyes, skin, inhalation of paint mist and paint vapour, should be strongly avoided.
- Recommended to use the product in well-ventilated area when applying the paint in insufficient ventilated areas, forced ventilation should be provided.
- Keep away from the reach of children.

For environmental safety: please donate the leftover paint and packaging to your local authorized institution for usage or recycling purpose.
Note: Wastes and empty containers should be disposed of in accordance with local regulations made under the Control of Pollution Act and the Environmental Protection Act.

Disclaimer:

To the best of our knowledge the technical data listed herein is true and accurate up to publication date and is subject to change without prior notice. User must contact Jazeera Paints Company to verify of any modifications before specifying or ordering the product. Thus, information given in this sheet is not intended to be exhaustive and any person using the product other than the recommendations in this sheet or without reverting to our Jazeera TSD, he should take his accountability in this connection.

As we are not capable to control the quality and the substrate's conditions as well as the factors that affect on using, or applying the product, so we never give any written or implied guarantee in these documents, but we guarantee our products to conform to Jazeera quality while we assume no responsibility for coverage, performance or injuries resulting from application. Liability "if any" is limited to replace the products mentioned above.