



Technical Data Sheet
JAZEERA PAINT REMOVER
JT-22002

Description:

A high quality paint remover, which contains special solvents for removing old paints from surfaces.

Recommended Use:

Recommended to use for removing enamel, nitrocellulose, polyurethane and some types of epoxy paints and other numerous types of coating applied on various surfaces.

Physical Constants:

- Color : Clear.
- Viscosity : 100 KU at 20°C.
- Specific Gravity: 1.2 ASTM D1475.

Application Guide:

- Apply one coat of “ Jazeera Paint Remover “ at a good thickness.
- Wait about (5-10) minutes until the old paint peels.
- Remove the peeled paint by using a putty knife.
- In case there is paint residue, apply another coat of the remover.
- Clean the surface from the remover trace after removing the paint completely.

Application Tools:

Brush , Putty knife.

Special Instructions:

- Can should not be shaken before use, allow to release the pressure slowly while unscrewing the lid of the can.
- Plastic, rubber surfaces in surrounding should be covered well, otherwise it will be destroyed.
- Use “Jazeera Paint Remover” in well-ventilated areas , use mask and gloves during application.
- In case the Remover comes in contact with the skin or eyes, wash it with plenty of water.
- Should be kept or handled away from children reach.

Packing:

US Gallon.

Shelf Life & Storage:

Shelf life : 12 months @ 25 °C.

Storage: The container should be kept in sealed, dry, cool, well ventilated place and stored in accordance with national regulations.

Handling and Safety:

- Handling: Handle with care. Stir very well before use.

• Health and safety: Please read and follow the precautionary notices displayed on the container, and all caution statements on the MSDS of this product. During application of paint, contact of liquid paint with eyes, skin, inhalation of paint mist and paint vapor should be strongly avoided. For spray application systems; applicator should wear protective clothing, gloves, also eye, skin and respiratory protection are always recommended. Keep away from reach of children.

• Ventilation: When used in enclosed areas, thorough air circulation must be used during and after application until the coating is cured. In addition, respirators must be used by all applicator.

Technical Data Sheet
JAZEERA PAINT REMOVER
JT-22002

- **Caution:** This product contains flammable solvents, keep away from sparks and open flame. For information on LEL and TLV, please read the MSDS.
- **Environmental safety:** Please donate the leftover paint and packaging to your local authorized institution for usage or recycling purpose.
- **Note:** Wastes and empty containers should be disposed of in accordance with local regulations made under the Control of Pollution Act and the Environmental Protection Act.

Disclaimer:

To the best of our knowledge the technical data listed herein is true and accurate up to publication date and is subject to change without prior notice. User must contact Jazeera Paints Company to verify of any modifications before specifying or ordering the product. Thus, information given in this sheet is not intended to be exhaustive and any person using the product other than the recommendations in this sheet or without reverting to our Jazeera TSD, he should take his accountability in this connection.

As we are not capable to control the quality and the substrate's conditions as well as the factors that affect on using, or applying the product, so we never give any written or implied guarantee in these documents, but we guarantee our products to conform to Jazeera quality while we assume no responsibility for coverage, performance or injuries resulting from application. Liability "if any" is limited to replace the products mentioned above.