

Technical Data Sheet
JAZEERA WOOD SEALER
J1-11004

Description:

One component acrylic solvent based sanding sealer for wooden surfaces it designed for high penetration and sealing wood to provide strong adhesion and good smoothness.

Recommended Use:

Recommended to use for interior applications as a clear sealer on all types of wooden surfaces such as doors, windows and furniture. Also it can be applied on "Jazeera Wood Stain".

Characteristics:

- Excellent filling properties and high fineness.
- Excellent sealing and sanding property.
- High adhesion properties .
- High durability.

Physical Constants:

• Finish:	Matt.	
• Color:	Clear.	
• Volume Solid:	45 %.	ASTM D2697.
• Viscosity:	130 KU @ 25°C	ASTM D562.
• Specific Gravity:	0.978 @ 25°C	ASTM D1475 .
• Flash Point:	Above 23°C.	

Surface Preparation:

- Remove all visible surface deposits such as grease, oils, dust, soils, salt and other contaminants. Make the surface smooth by sanding with sand paper and clean it well prior to application.
- Patch all holes and imprefictions with (Jazeera Wood Filler) and sanding.

Application Condition:

- Temperature during application should be more than (5°C).
- Surface temperature: at least (3°C) above dew point.
- Relative humidity: maximum 85%.

Painting System :

Primers:

- For natural wood appearance, apply Jazeera Wood Sealer.
- For colored wood appearance, apply "Jazeera Wood Stain" before sealer.

Topcoats: Can be overcoated by any of acrylic solvent based topcoats.

Application Method and Thinning:

THINNER: Recommended thinner is "Jazeera Thinner 507".

Application Method	Airless Spray	Air Spray	Putty Knife	Brush/Roller**
Thinning (by volume)*	(0 - 5)%	(20-25) %	(0-5) %	(10-15) %
Nozzle Orifice	0.011 - 0.015"	(1.5-1.8)mm	N/A	N/A
Nozzle Pressure	7.86 MPa (1100psi)	29.0-43.5 psi	N/A	N/A
Spray Angle	40-65°	50-80°	N/A	N/A

* Depends on the weather condition at work place.

** Recommended for stripe coat and small areas.

Technical Data Sheet
JAZEERA WOOD SEALER
J1-11004

Film Thickness and Spreading Rate:

	Minimum		Maximum		Recommended	
	(μm)	mil	(μm)	mil	(μm)	mil
Dry Film Thickness (DFT)	35	1.4	80	3.2	50	2
Wet Film Thickness (WFT)	77.8	3.1	177.8	7.1	111.1	4.4
	m2/l	ft2/USgal	m2/l	ft2/USgal	m2/l	ft2/US gal
Theoretical Spreading Rate	12.8	515	5.6	226	9	361

Drying Time and Recoating:

Drying times are generally related to air circulation, temperature, film thickness and number of coats, and will be affected correspondingly.

- Temperature 25°C/77°F
- Relative humidity 50%
- Surface dry 30 min.
- Hard dry 1 hour
- Full cure 7 days
- Dry to recoat, minimum 3-4 hours
- Dry to recoat, maximum* -----

Note: All records given in the table are typical at: recommended film thickness, good ventilation and one coat system.

*The surface should be dry and clean prior to application. If the recoating interval is exceeded, the surface may need to be roughened

Packing:

Packed in: US Gallon 3.6 Ltrs

Shelf Life & Storage:

Shelf Life : 24 months @ 25 °C.

Storage: Store indoors. Storage conditions are to keep the container in sealed container in dry, cool and well ventilated place.

Handling and Safety:

- Clean up: Use "Jazeera Thinner 507" for cleaning tools and in case of stains while application.
- Handling: Handle with care. Stir very well before use.
- Health and safety: Please read and follow the precautionary notices displayed on the container, and all caution statements on the MSDS of this product. During application of paint, contact of liquid paint with eyes, skin, inhalation of paint mist and paint vapor should be strongly avoided. For spray application systems; applicator should wear protective clothing, gloves, also eye, skin and respiratory protection are always recommended. Keep away from reach of children.
- Ventilation: When used in enclosed areas, thorough air circulation must be used during and after application until the coating is cured. In addition, respirators must be used by all applicator.
- Caution: This product contains flammable solvents, keep away from sparks and open flame. For information on LEL and TLV, please read the MSDS.
- Environmental safety: Please donate the leftover paint and packaging to your local authorized institution for usage or recycling purpose.
- Note: Wastes and empty containers should be disposed of in accordance with local regulations made under the Control of Pollution Act and the Environmental Protection Act.

Disclaimer:

To the best of our knowledge the technical data listed herein is true and accurate up to publication date and is subject to change without prior notice. User must contact Jazeera Paints Company to verify of any modifications before specifying or ordering the product. Thus, information given in this sheet is not intended to be exhaustive and any person using the product other than the recommendations in this sheet or without reverting to our Jazeera TSD, he should take his accountability in this connection.

As we are not capable to control the quality and the substrate's conditions as well as the factors that affect on using, or applying the product, so we never give any written or implied guarantee in these documents, but we guarantee our products to conform to Jazeera quality while we assume no responsibility for coverage, performance or injuries resulting from application. Liability "if any" is limited to replace the products mentioned above.