

1. PRODUCT & COMPANY IDENTIFICATION

PRODUCT NAME PRODUCT CODE PRODUCT DESCRIPTION RECOMMENDED USE	JAZEERA FLOREX MB- Part B JI-68039H See Technical Data Sheet See Technical Data Sheet	
COMPANY IDENTIFICATION	See Technical Data Sheet	
COMPANY NAME: COUNTRY:	JAZEERA FACTORY FOR PAINTS CO. SAUDI ARABIA	
CITY:	KHAMIS MUSHAYT.61961	
P.O. BOX:	1900	
TEL:	+ 966 17 221 1111	
FAX:	+ 966 17 238 2728	
2. COMPOSITION / INFORMATION O	N INGREDIENTS	
MATERIAL OR COMPONENT	CAS NO OSHA PEL AGGIH TLV WT%	
Polyisocyanates Polyisocyanates Polyisocyanates	9016-87-9 N/A 0.005PPM 40-60 101-68-8 30-60 30-60 5873-54-1 10-30 10-30	
3. HAZARD IDENTIFICATION		
HUMAN AND ENVIRONMENTAL HA	AZARDS:	
Flammability:	Flammable	
Effects of Exposure:	Heated product may produce inhalable	
Skin Irritation:	Irritant	
Eye Irritation:	Irritant	
Breathing Irritations	Irritant to respiratory system	

Irritant to respiratory system



4. FIRST AID MEASURES

Eyes Contact Skin Contact	Immediately flush eyes with fresh water at least 15 times. Contact a physician. Wash with soap and water, remove contaminated clothing and launder before re-use.
Ingestion	If conscious, give plenty of water to drink do not induce vomiting Contact a physician.
Inhalation	Remove to fresh air, give oxygen and/or artificial respiration if required. Contact a physician.
Others	Referral to a physician is recommended if there is any question about the seriousness or any injury

5. FIRE FIGHTING MEASURES

Flash Point Extinguishing Media Fire Fighting Procedure Unusual Fire/Explosion Hazard 227 ° C ASTM D-56
Water Jet, CO₂, Dry Chemical, Foam.
Use self contained- breathing apparatus.
Decomposition and composition product may be toxic.

6. ACCIDENT RELEASE MEASURES

SAFETY PRECAUTION

- Open enclosed spaces to outside atmosphere.
- Wear protective clothings, boots, gloves & eye protection.
- Consult the safety measures listed under headings 7 & 8.

SPILL RELEASE PROCEDURES:

Remove spillage by absorbing in nonreactive absorbent material.

WASTE DISPOSAL METHODS:

Consult qualified local or corporate personnel for method that will comply with local, state and federal health and environmental regulations.

7. HANDLING & STORAGE

Handling & Storage Precautions

Keep container closed upright when not in use. Store in cool, dry, well ventilated area.

- Avoid storage temperature above 100 Degrees Fahrenheit.
- 8. EXPOSURE CONTROL / PERSONAL PROTECTION

Respiratory Protection

Use NIOSH approved organic vapor cartridge respirator when vapor/mist exposure is likely. Use air-line respirator in confined or restricted ventilation areas. Refer to 29 CFR, OSHA parts 1910, 1915, and 1916 for coating operations.



Ventilation

General mechanical and local exhaust in accordance with ACGIH recommendations. **Protective Gloves**

Wear impermeable gloves.

Eye Protection

Wear splash-proof chemical goggles

9. PHYSICAL AND CHEMICAL PROPERTIES

Specific Gravity	0.9-0.97 water = 1	
Solubility	Aromatic Hydrocarbon, Alcohol, Ester, Ether, Ketone.	
Insolubility	Water, Aliphatic Hydrocarbon.	
Odor	Organic Solvent.	
Appearance	Liquid Clear	
VOC % by volume	0 %	

10. STABILITY AND REACTIVITY

Stability	Stable
Stability Condition to Avoid	Elevated temperature
Materials to Avoid	Strong oxidization agents, mineral acids, and bases
Hazardous Decomposition Prod	ucts Carbon monoxide, Carbon dioxide, and Oxides of Nitrogen
Polymerization	Will not occur

11. TOXICOLOGICAL INFORMATION

No toxicological information is available for this product.

12. ECOLOGICAL INFORMATION

Biological degradability Not readily biodegradable

13. DISPOSAL CONSIDERATION

Spill Release Procedure

Avoid breathing of vapors or dust. Use absorbent clean-up materials or sweep up. Place in separate container. Keep out of public sewers & waterways. If entry is threatened or occurs, notify local authorities. Eliminate all sources of ignition.



Waste Disposal Methods

In separate closed metal container in accordance with all applicable regulations.

Handling & Storage Precautions

Keep container closed upright when not in use. Store in cool , dry , well ventilated area. Avoid storage temperature above 100 Degrees Fahrenheit.

Other Precautions

Do not take internally. Avoid prolonged breathing of vapors or dust or spray mist or contact with skin & eyes. Do not weld or flame cut an empty container. Ground containers when pouring. Destroy contaminated leather & absorbent shoes.

14. TRASPORT INFORMATION

T Land Transport (ADG)

Class : 3 Labeling of vehicles – hazard code : 90 UN No. :1263 Symbol of hazard : 3 **Sea Transport (IMDG)** IMO PSN Code : LCT IMO Proper Shipping name : Paint or Paint related material. UN Hazard Class : 3 UN Number1263 **Air Transport (IATA)** IATA Label : Flammable liquid. Symbol of Hazard : 3 UN Hazard Class : 3 UN Number1263

15. STATUTORY / REGULATORY INFORMATION

According to the regulations, the following danger labeling of the product is required.

- The Text Flammable
- Danger labeling Xi and N, Dangerous for environment.

R Phrases

- R 36/38 Irritating to eye & skin
- R 43 May cause sensitization by skin contact.
- R 51/53 Toxic to aquatic organisms.

S Phrases

- S 7/9 Keep container tightly closed in well ventilated place.
- S 28 After contact with skin, wash immediately with plenty of soap & water.
- S 36/37/39 Wear suitable clothing , gloves and eye/face protection.
- S 61 Avoid release to the environment.



16.OTHER INFORMATION

- Since the end users working conditions are not known by us the information provided in this safety data sheet is based on our current level of knowledge.
- The information provided in this safety data sheet relates to the product in the state in which it is delivered.
- It is intended to describe our products from the point of view of safety requirements & is not intended to guarantee any particular properties.
- The product must not be used for any purpose other than those specified under heading without first obtaining written handling instructions.
- It is all times the responsibility of the users to take all necessary measures to comply with legal requirements & local regulations.
- The information given in this safety data sheet must be regarded as a description of the safety requirements relating to our product and not guarantee of its properties.