دهانات الجزيـرة
Jazeera Paints

Technical Data Sheet
JAZEERA DURA MATT
JA-15069

Description:
A fully transparent water borne protective matt paint, based on acrylic polymer. It creates a thin barrier that increases water and stain resistance thanks to its special formula.

Recommended Use:
Recommended to use for interior applications over any topcoat that applied by trowel or spray from Jazeera Paints.

Characteristics:
- Provides full transparent finish.
- High intensity and durability.
- Resistance to different weather conditions.
- High flexibility.
- Excellent water resistance.
- Exhibits excellent stain resistance.
- Good washability.

Physical Constants:

• Color	Clear.		
• Specific Gravity	1.03 @25°C.	ASTM D1475	
• Viscosity	70 KU ± 3 @30°C.	ASTM D562	
• Volume Solid	32%	ASTD2697	
• D.F.T.	20 µ each coat.		
• Theoretical Spreading Rate	16 m^2/L.		
• Freeze-Thaw Stability	Pass 3 cycles	ASTM D2243	
• Heater Stability	Pass 49 days at 50°C	ASTM D1849	
Tests:			
• VOC	4.84 g/L	ASTM D2369-24 / SCAQMD Rule 1113	METS - UAE
• VOC Emission After Application	Pass	LEED Requirements - Ver.4	METS - UAE

*The practical spreading rate of the product depends on the design, thickness of the coat, nature of the surface and application conditions. (To avoid waste, be sure to buy the right amount of the paint for the required surface area)

Application Guide:
- Make sure that the surface is clean, dry, free from dust, oil, grease, powder, salt and mold.
- The required temperature during application, must not be less than 5°C; the surface moisture should not exceed 8% and the relative humidity at work place should not exceed 70%.
- pH of surface should not exceed 9.
- Paint should be stirred carefully before use.
- Do not apply on wet and moistened surfaces until completely dry, avoid application in rainy and high humidity climate.
- Do not apply the next coat unless the previous one is fully dry. Minimum recoating interval time should be followed.
- Adequate ventilation should be provided during applicaion time.

Application Tools:
- Roller: Velvet Roller 1063.

Thinner:
Tap water.

Thinning Ratio:
30-50%

Issued: 11/2026

دهانات الجزيـرة
Jazeera Paints

Technical Data Sheet
JAZEERA DURA MATT
JA-15069

Painting System:
• Apply 2 coats of “Jazeera Dura Matt” over any interior topcoat that applied by trowel or spray from Jazeera Paints.

Drying Time:

• Surface dry	30 min.
• Hard dry	3 hours.
• Recoating Interval	8 hours. (minimum)
• Full cure	7 days.

All above test results according to ASTM D5895@25°C.

Cleaning Tools:
Tap water.

Packing:
Drum 18.0L
Gallon 3L

Shelf Life & Storge:
Shelf life : 12 months @ 25 °C.
Storage: The container should be kept in sealed, dry, cool,
well ventilated place and stored in accordance with national regulations.

Safety Precautions:
Please read and follow the precautionary notices displayed on the container, and all caution statements on the MSDS of this product.
• Handle with care before and during use.
• During application of paint, contact of liquid paint with eyes, skin, inhalation of paint mist and paint vapour, should be strongly avoided.
• Recommended to use the product in well-ventilated area when applying the paint in insufficient ventilated areas, forced ventilation should be provided.
• Keep away from the reach of children.
For environmental safety: please donate the leftover paint and packaging to your local authorized institution for usage or recycling purpose.

Disclaimer:
To the best of our knowledge the technical data listed herein is true and accurate up to publication date and is subject to change without prior notice. User must contact Jazeera Paints Company to verify of any modifications before specifying or ordering the product. Thus, information given in this sheet is not intended to be exhaustive and any person using the product other than the recommendations in this sheet or without reverting to our Jazeera TSD, he should take his accountability in this connection.
As we are not capable to control the quality and the substrate's conditions as well as the factors that affect on using, or applying the product, so we never give any written or implied guarantee in these documents, but we guarantee our products to conform to Jazeera quality while we assume no responsibility for coverage, performance or injuries resulting from application. Liability "if any" is limited to replace the products mentioned above.

Issued: 11/2026